



Douglas Fir Picture windows

Loewen

PICTURE/DIRECT SET WINDOWS



Loewen Picture/Direct Set windows are non-operating units designed to provide maximum views with a minimum of wood framework.

PRODUCT FEATURES

STANDARD FEATURES

- Natural, clear Douglas Fir interior (no visible finger joints)
- Frame construction designed for 4 9/16" (116 mm) jamb
- Low E² insulated glazing with 1/2" (12 mm) airspace
- Extruded aluminum cladding in nine standard colors, primed wood or clear Fir exterior

GLAZING:

Heat-Smart® 1, 2 and 3, Tranquility®, StormForce™ DP, IP, MP.

SIMULATED DIVIDED LITES (SDL) AND GRILLES:

SDL — 3/4" (19 mm), 1 1/8" (29 mm), 2" (50 mm), Removable Grilles.

BRICKMOULD:

2" (50 mm), 3 1/2" (89 mm) and 5 1/2" (140 mm) wood. 2" (50 mm) and 3 1/2" (89 mm) metal.

METAL CLAD COLOR SPECTRUM:

Nine Standard Palette and 27 optional Architectural Palette colors. Available in **Cyprium Collection** (see Section L page 23).



For a more in-depth, comprehensive review of **Product Features**, please refer to the **Miscellaneous section**.



Visit the **Loewen Photo Gallery** online at www.loewen.com/home.nsf/info/gallery for a large collection of Loewen product and elevation photography.

Specifications and technical information are subject to change without notice. Metric and Imperial measurements are converted accurately, however in some cases industry conventions cause a 1 mm variance. (Example: 3/4" is shown as 20 mm for all glass measurements as this is the industry standard.)

LEGEND: ● — STANDARD
○ — OPTIONAL

1 – Nine standard metal clad colors, 27 optional

2 – Some size restrictions apply

Picture/ Direct Set

Variables	
Durability:	
Low Maintenance Metal Clad Exterior	● ¹
Clear Douglas Fir Exterior Finish	●
Clear Mahogany Exterior Finish	○
Primed Exterior Finish	●
Performance:	
Heat-Smart® Plus 1	●
Heat-Smart® Plus 2, 3 ²	○
Tranquility®	○
StormForce™	○
Appearance:	
SDL	○

All standard window configurations are represented in this **Loewen Architectural Catalog**. Numerous custom opportunities exist — please contact your Authorized Loewen Dealer.



Picture/Direct Set Windows

C3

www.loewen.com

SPECIFICATIONS

STANDARDS

Units have been tested by an independent laboratory for air and water infiltration and thermal performance requirements.

FRAME

Manufactured from Coastal Douglas Fir kiln-dried lumber with frame construction designed for 4 9/16" (116 mm) jamb. All exterior components are factory primed; minor scratches or abrasions are not considered defects.

ALTERNATE SPECIES

The entire Loewen product line is also available in optional Mahogany (*Swietenia macrophylla*) or optional FSC chain of custody certified Douglas Fir (SW-COC-1739).

PRESERVATIVE TREATED

All wood parts are dipped in approved preservative.

GLAZING

A wood stop combined with glazing materials ensures a positive seal.

INSULATING GLASS

Double or triple glass configurations with 1/2" (12 mm) airspace.

HEAT-SMART® Plus Systems 1, 2 and 3

Heat-Smart® best describes the benefits of the product that incorporates Low E² coating and argon gas. Heat-Smart® systems help reduce heating and cooling costs, providing superior energy efficiency.

SIMULATED DIVIDED LITES (SDL) AND GRILLES

Standard SDL come without airspace grilles. Optional airspace grilles available. Grille bars are permanently applied to the interior and exterior.

Loewen natural clear wood grilles install from the inside of the house and are removable for cleaning.

Note: Optional Grilles

Natural wood grilles will be supplied unless otherwise specified.

METAL CLADDING

Heavy duty extruded aluminum exterior metal cladding is available in nine Standard Palette and 27 optional Architectural Palette colors. Interior of window remains a natural wood finish as a standard. Metal clad units are supplied ready-to-install complete with nailing flange.