

SafeGard™

CASEMENT-WINDOW
OPENING CONTROL DEVICE

Industry's First Casement –
Window Opening Control Device

SafeGard™ Provides Peace Of Mind On Casement Window Applications.

As a market leader in fenestration hardware, Truth has engineered, patented and manufactured the industry's first casement – Window Opening Control Device (W OCD) that meets the requirements of ASTM F2090-10. This innovative hardware system provides safe and secure operation of egress style windows critical in today's building projects. Multiple safe guards are in place to help control the window opening to prevent accidental falls while at the same time allowing easy operation in the event of an emergency. Typical operation limits the opening of the sash to less than 4". An additional operation is required to open the window fully for egress purposes. This additional operation can be performed without the use of keys, or special tools and the SafeGard™ casement – W OCD will automatically re-latch when the sash is fully closed.



Loewen

To find your nearest loewen dealer go to www.loewen.com or contact us at:

E-mail:
info@loewen.com

Canada and U.S.A.:
1.204.326.6446

International:
1.800.563.9367

Easy Installation And Operation —

Tested And Certified To ASTM F2090 -10.

Tested And Certified

The SafeGard™ casement – WOCD is tested and certified to ASTM F2090-10 which is the standard specification for Window Fall Prevention Devices with Emergency Escape (Egress) Release Mechanisms. The ASTM F2090-10 addresses window fall prevention that helps protect against potential falls by children through open windows.

Easy Installation: Designed to allow for factory installation as well as field installation by trained personnel.

Robust Design: Made entirely of austenitic stainless steel and plastic.

Versatile Application: Fits in standard hinge cavity for easy installation.

Easy Operation: No keys or special tools needed.

SafeGard™

CASEMENT-WINDOW
OPENING CONTROL DEVICE

Operation: 4 Easy Steps



Step 1. Unlock window and crank open to limit.



Step 2. Slide red cover up and hold.



Step 3. Rotate the orange tab toward the exterior (if tab is difficult to rotate, relieve pressure using the crank).



Step 4. Continue to crank window open while holding the orange tab in place, until the window is fully opened.

Warranty: Protected under the terms of the Truth Warranty for Window & Door Manufacturers and Authorized Distributors. Refer to Truth's Terms and Conditions for further details.

Loewen