

Double Hung



INSPIRED BY YOU



Double Hung, interior view

The Loewen Double Hung is the epitome of Classic American Architecture – authentic and charming. Through years of research, design, and consultation with architectural experts, we were able to seamlessly blend traditional aesthetics with leading-edge technology.

The Loewen Double Hung is constructed with Coastal Douglas Fir or Mahogany to create a beautiful natural wood interior. The exterior can be specified with low maintenance, extruded aluminum cladding or natural wood. Both the interior and exterior are available as primed. All configurations present authentic details such as stile and rail aesthetics, tall bottom rail, narrow checkrail, and a hidden jamb liner.

Thanks to the innovative balance system, Loewen Double Hung windows open and close smoothly. A single-handed lock/tilt mechanism allows for inward tilting of the sash for easy cleaning – or complete removal. Luxury grade hardware is standard on all Double Hung units in a variety of finishes. Complementary sash lifts (optional) add layers of depth and character for the most exacting projects.

CALL FOR THE DEALER NEAREST YOU.

Canada and U.S.A
1.800.563.9367

International
1.204.326.6446

E-mail:
info@loewen.com



Hidden jamb liner with traditional flush checkrail and square frame edge



Traditional head with removable head parting stop



Luxury grade, optional sash lifts (shown in Antique Brass)



Luxury grade lock and keeper (shown in Antique Brass)



Historic tall bottom rail, 2" brickmould and standard sill nosing



Williamsburg casing (also available in non-clad units)



Double Hung, exterior view

PROGRESSIVE PERFORMANCE

We've combined superior strength and durability with leading manufacturing techniques and innovative efficiency options to deliver a window that not only matches the look of your residence, but also delivers the progressive performance it deserves.

- Innovative balance system allows windows to open and close smoothly
- Single-handed lock/tilt mechanism allows for inward tilting of the sash for easy cleaning
- Integrated structural sill block and metal nailing flange allows for enhanced moisture management and maximum protection against water infiltration
- Triple glazed option for maximum energy efficiency
- Thermally broken aluminum sill for improved energy efficiency

SUPERIOR DESIGN

- Integrated glazing leg
- Extruded aluminum cladding
- Authentic stile and rail aesthetics
- Hidden corner and sill keys
- Full and half-screen options
- Optional jamb jacks for improved site installation
- Removable jamb covers for serviceability
- Unified jamb tracks
- Liberty (non-tilting) option available with removable stops
- Impact tested (Liberty option)

WOOD SPECIES

Double Hungs are available in standard Douglas Fir, or optional Handuran Mahogany.

METAL CLAD COLOR SPECTRUM

Choose from a variety of standard, architectural and custom colors.

CASING AND SILL NOSINGS / SUBSILLS

- Clad casing: 2" brickmould, 3 1/2" flat casing, Adams and Williamsburg
- Clad sill nosing: standard, BC, Heritage, and Multi-unit (flush frame)
- Wood casing: 2" brickmould, 3 1/2" & 5 1/2" flat casing, Adams and Williamsburg
- Wood subsill: Standard, BC and Heritage

HARDWARE FINISHES

Double Hung locks, keepers, and sash lifts are available in linen, bronze, sandstone, black, bright brass, antique brass, brushed chrome, satin nickel and oil rubbed bronze.

GLAZING

- Standard is Heat-Smart® (Low-E2) insulated glazing with 1/2" (12mm) air space; optional upgrades to Heat-Smart® X, Heat-Smart® T or Heat-Smart® XT
- Decorative glass and custom glazing options available
- Simulated Divided Lites (SDLs) available in 3/4", 1 1/8" and 2" widths
- Standard for SDLs to have internal spacers, where possible

For full details, contact your Authorized Loewen Dealer.

Trademarks owned by C.P. Loewen Enterprises Ltd. Used under license ©C. P. Loewen Enterprises Ltd. All rights reserved. Information subject to change without notice.